

# SLIP NO MORE

## Anti Slip Treatment Cleaner/Maintainer



SNM Anti Slip Treatment Cleaner/Maintainer is formulated to provide the cleaning and soil suspension properties necessary to effectively clean and maintain positive slip resistant characteristics in restaurant and food service areas, restrooms, nursing homes, hospitals, and light industrial manufacturing facilities where food, protein-based soils, light oils, and dirt can cause slippery conditions. Extensive laboratory and field testing on various types of flooring (including ceramic and stone tile, sealed wood, and concrete) has demonstrated this product's ability to raise the coefficient of friction readings beyond those required by the Occupational Safety and Health Administration and the 0.6 SCOF recommended by the National Floor Safety Institute, ANSI and Americans With Disabilities Act.

### APPLICATION & MAINTENANCE

Dilute SNM Anti Slip Treatment Cleaner/Maintainer with warm water at the following dilutions, depending on the degree and type of soil to be removed:

Light Duty Cleaning: 6 ounces SNM Anti Slip Treatment Cleaner/Maintainer per gallon of water (1:21).

Medium Duty Cleaning: 8 ounces SNM Anti Slip Treatment Cleaner/Maintainer per gallon of water (1:16).

Heavy Duty Cleaning: 12 ounces SNM Anti Slip Treatment Cleaner/Maintainer per gallon of water (1:10).

Apply with either an autoscrubber or by damp mopping. In order to avoid redepositing grease and protein soils when damp mopping, a two bucket system in which one bucket contains the SNM Anti Slip Treatment Cleaner/Maintainer and one bucket is used for soiled solution, should be used. Heavy deposits of protein soil, dirt, or grease may be addressed by applying SNM Anti Slip Treatment Cleaner/Maintainer at 16 ounces per gallon using a pressurized sprayer, watering can, or mop. Scrub the area with a stiff bristle brush or buffing machine, remove the soiled solution with a wet vacuum or mop, and finish the cleaning procedure by damp mopping. Allow the floor to dry. Do not rinse.

### SPECIFICATIONS

Active Ingredients	Synthetic and Alkaline Detergents, Slip Resistant
pH	11.0-12.0
Free Ammonia	None
Free Alkali	None
Free Acid	None
Phosphates	None
Abrasives	None
Color	Blue
Odor	Moderate
Solubility in Water	Complete
Freeze/Thaw Stability	3 cycles
Shelf Life	1 year minimum at room temp.
Flash Point	>200°F
Weight Per Gallon	8.5 lbs
Biodegradable	Yes
Soil Suspension	Excellent

### SAFETY INFORMATION

Health	2
Flammability	0
Reactivity	0
Personal Protection	B

Read Safety Data Sheet thoroughly before using.



**IRRITANT WARNING:** Contains 2-Butoxyethanol CAS# 111-76-2, and 2-Amino Ethanol CAS# 141-43-5, alkaline detergents which may cause irritation in undiluted concentrations. Protective eye glasses and gloves should be worn during use.

**FIRST AID:** In the event of skin or eye contact, flush thoroughly with clean water for 15 minutes. If skin irritation occurs seek medical attention. In the event of eye contact or ingestion seek immediate medical treatment.



**Manufactured For And Distributed by:**  
**Innovative Floor Safety Products, LLC**  
**Tel: 702-478-6932**  
**Website: [www.officialslipnomore.com](http://www.officialslipnomore.com)**