


SLIP NO MORE II Anti Slip Treatment

SNM II Anti Slip Treatment's advanced chemistry provides a one step slip resistance enhancing treatment and cleaner in the same product. SNM II Anti Slip Treatment can be used on all types of stone flooring, including Terrazzo, Marble, Quarry Stone, Blue Stone, Mexican Tile, Ceramic Tile and Granite. At the higher recommended concentration, a single application of SNM II Anti Slip Treatment creates a micro-profile on any type of stone flooring, significantly increasing slip resistance characteristics. When used at lower concentrations, SNM II Anti Slip Treatment can be used

to effectively clean stone floors in restaurants, cafeteria's, food courts, restrooms, and entrances and walkways, while maintaining positive slip resistance characteristics. SNM II Anti Slip Treatment can be applied with either a mop or automatic scrubber and will not cause a build-up with routine use. Field use has produced an average increase in slip resistance of .1 SCOF per application. SNM II Anti Slip Treatment helps any type of stone floor meet or exceed the slip resistance recommendations of the U.S. Occupational Safety and Health Administration (OSHA), National Floor Safety Institute (NFSI) and American National Standards Institute (ANSI).



APPLICATION & MAINTENANCE

To Instantly Increase Slip Resistance Characteristics: Dilute 128 ounces of SNM II Anti Slip Treatment per gallon of clean water (1:1). Apply the diluted solution using a mop and wringer bucket or plastic watering can, making sure to thoroughly and uniformly wet out the area to be treated. Work in manageable size areas to avoid the solution drying out. Allow the solution to stand and work for approximately 10-15 minutes. Remove the solution with a wet vacuum, automatic scrubber or mop and wringer bucket. Lightly damp mop the treated area with a solution of neutral cleaner or clean water.

For Routine Cleaning: Dilute 4 ounces of SNM II Anti Slip Treatment per gallon of clean water. Apply the diluted solution with either an autoscrubber or by damp mopping using a mop and wringer system. In order to avoid redepositing soils when damp mopping, a two bucket system in which one bucket contains the SNM II Anti Slip Treatment and one bucket is used for soiled solution, should be used. Allow the floor to dry.

SPECIFICATIONS

Active Ingredients	Synthetic and Alkaline Detergents, Slip Resistant Additive
pH	6.0 - 7.0
Slip Resistance (ASTM)	>.6 (SCOF)
Free Ammonia	<4%
Free Alkali	None
Free Acid	None
Phosphates	None
Abrasives	None
Color	Blue
Odor	Green Apple
Solubility in Water	Complete
Freeze/Thaw Stability	3 cycles
Shelf Life	1 year minimum at room temp.
Flash Point	>200°F
Weight Per Gallon	8.5 lbs
Biodegradable	Yes
Soil Suspension	Excellent

SAFETY INFORMATION

Health	1
Flammability	0
Reactivity	0
Personal Protection	B

Read Safety Data Sheet thoroughly before using. SNM II Anti Slip Treatment is not a hazardous mixture as defined in 29 CFR 1910.1200. Safety Glasses and Gloves should be worn during application. Contains Glycol Ethers. Can cause eye irritation. Prolonged exposure may cause skin irritation. **FIRST AID:** In case of contact, flush with plenty of water. If swallowed, get immediate medical attention.



**Manufactured For And Distributed by:
Innovative Floor Safety Products, LLC
Tel: 702-478-6932
Website: www.officialslipnomore.com**